


FED. SUP. CLASS
5940

DASH NO.	SCREW SIZE	HOLE DIA A		B	AWG SIZE
		MAX	MIN		
1	10	.205	.193	27/32	12
2	12	.236	.221	27/32	TO
3	1/4	.285	.258	55/64	20

MATERIAL: PHOSPHOR BRONZE (1.25% TIN). GRADE E, NO. 502.

FINISH: HOT TIN DIP OR ELECTRO-DEPOSITED TIN ALL OVER, MINIMUM THICKNESS .0005.

NOTES: 1. ALL DIMENSIONS IN INCHES. TOLERANCE: FRACTIONAL $\pm 1/64$; UNLESS OTHERWISE SPECIFIED.

2. MAXIMUM BURR OF .005 IS ALLOWABLE.

3. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

4. THE MS PART NUMBER CONSISTS OF THE MS NUMBER PLUS THE DASH NUMBER.

5. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

P.A.	MU	TITLE	TERMINAL, LUG, SOLDER TYPE, PHOSPHOR BRONZE STAMPING, LOCKING TYPE, 30°, ONE HOLE	MILITARY STANDARD
Other Cust	SH			MS 77069
	11			
PROCUREMENT SPECIFICATION MIL-T-15659		SUPERSEDES:		SHEET 1 OF 1

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have furnished, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all engineering and design applications and for repetitive use shall be made from this document.

REVIEW INTEREST ARMY: MU
NAVY: SH
AF: 11

USER INTEREST ARMY
NAVY

APPROVED 8 Sep 65 REVISED